

F9310

Model No.	OEM-F9310	
Use Case	Data/Image Processing	
Feature	Description	Specifications
Chassis	1U Rack-mount	H x W x D: 1.75" x 19" x 25.9" (44.5 x 482.6 x 657.9mm)
	Internal Bay(s)	1x – M.2 M-Key Gen 3 x4 2280
	External Bay(s)	10x – 2.5" SATA/SAS drive bays
Motherboard	Chipset	Intel® 621A
	Processor	3 rd Gen Intel® Xeon™ Scalable processors, Single socket LGA-4189 supported. - Intel® Xeon® Gold 6326 - Intel® Xeon® Silver 4314
	Memory	8x – DDR4 3200MHz ECC system memory
	Rear I/O	2x – GbE NICs (RJ45) 1x – Mgmt port 4x – USB 3.0 ports (Type A) 1x – VGA 1x – Serial port (RS232)
	Front I/O	2x – USB 3.0 ports (Type A)
	Expansion	1x – PCIe 3.0 x16 FH (single-width)
Power Supply	650W 100-240VAC 50-60Hz 80+ w/ IEC inlet (1+0 or 1+1)	
O/S	Microsoft Windows 10/11Server, RHEL	
Certifications	CE, FCC Class A, UL	Purchase Lifecycle: June, 2022 – 2027



* Picture(s) may not represent all available options