TVI7502X NAS



CDII	Tetal Time Lel. IF 11967
CPU	Intel Tiger Lake I5-1135G7
Memory	2* DDR4 SODIMM
Storage	3* Key-M M.2 socket for SSD (2 are PCIE X2 SSD, the other is PCIE X1 SSD)
	12*SATA (2 ASM1166 out, the interface is mini SAS)
Extension	1*M.2 Key-E for WIFI socket, co-lay with PCIE X1 SSD socket (choose with resistance)
1/0	2* Dual Layer Type-A USB2.0 port
	1* RJ45 for 2.5Gb LAN
	1* RJ45 for 10Gb LAN
	2* TBT4 (no power supply function required)
	1* Power button
	1* Copy button
	1* HDMI
	1* TF card holder
Pin header	1* F_PANEL pin header (including network card indicator and hard disk indicator, hard disk indicator is
	controlled by GPIO)
	4* 2.54mm fan holder (1 is for CPU fan holder, the other 3 use the same controller)
	2* USB2.0 pin header
	3* MINI SAS socket (can support 12 SATA hard drives)
Power supply	300W ATX power supply
Environment	Operating temperature: -10~50°C. Storage temperature: -20~60°C, relative humidity 95%
Dimension	310mm*305mm*221mm
Weight	9. 5KG