



Pictures show sample configurations, real product may vary.



## COMPUTER UNIT

Processor	Intel® Core™ i3-12100, Intel® Core™ i5-12500 or Intel® Core™ i7-12700
Chipset	Intel® W680
Memory	DDR5
LAN	2 x 1 GbE Intel® i210 2 x 10GbE Intel® X710
Remote Management	IPMI ASPEED AST2600 (dedicated LAN port) with iKVM, vMedia support
Operating system	Windows® 10 IoT Enterprise
Expansion Slots	1 x PCIe x16 LP* 2 x PCIe x4 LP* 1 x PCIe x1 LP*
Front I/O	2 x USB 3.2 4 x RJ-45 2 x Displayport 1 x DVI-D 1 x VGA 1 x COM AC-in Power button
Cooling	Active

## POWER

\* low profile

Power supply	100-240 V AC
Power consumption	3 A

## SYSTEM

Dimensions (WxDxH)	17.0 x 11.8 x 3.5 in
Material	Steel, RAL 9005 powder coated
Weight	Approx. 8 kg
Mounting	2U rackmount

## ENVIRONMENTAL CONDITIONS

	Storage	Operating
Temperature	-20°C to +60°C	0°C to 35°C
Humidity	10% to 95% <sup>1</sup>	10% to 80% <sup>1</sup>

<sup>1</sup> non-condensing

## CERTIFICATIONS

CE

## DIMENSIONS

Pictures show sample configurations, real product may vary.

