



X50V7

FANLESS 15.6" ALL-IN-ONE PC

FOR POS, POI, KIOSK APPLICATION



FANLESS



IP54



TOUCHSCREEN



VESA MOUNT

Shuttle X50V7 is an All-in-One PC boasting a 15.6-inch 16:9 touch screen and equipped with Intel® 8th Gen Celeron® 4205U dual-core processor. The Whisky Lake architecture helps deliver outstanding performance while increasing energy efficiency. Passive cooling and the IP54 front panel make the system virtually noise-free, maintenance-free, and ensure a highly stable 24/7 operation. Besides, with flexible expansion options, users can easily upgrade their device with COM, LPT, and DIO ports. Available in black and white to suit a variety of POS, POI, and Kiosk applications.

FEATURES

- 8th Gen. Intel Celeron Processor
- IP54 compliant front panel
- 24/7 certified in 0-40 ° C environments
- Supports triple display via HDMI and VGA
- Excellent Connectivity: 4x USB 3.2 Gen 1, 2x USB 2.0, 2x RS232, 1x SD card
- Two expansion options: RS232 and Parallel expansion card



- | | | | | |
|------------------------------|--------------------------|-----------------------------|----------------------------------|--------------------------|
| A Webcam | D Power LED | G USB 2.0 ports | J HDMI out | M D-Sub (VGA out) |
| B Microphone | E Power Cord Hook | H LAN Port | K Microphone Jack | |
| C Hard Disk Drive LED | F DC in | I USB 3.2 Gen1 ports | L Headphone/Line out Jack | |

SPECIFICATIONS

Model		X50V7
Color		Black/White
Screen		15.6" LCD (16:9, HD 1366 x 768) Single touch
CPU		Intel® Celeron 4205U
Video Engine Processor		Intel® UHD Graphics
Max Resolution		HDMI 4096 x 2304@30Hz VGA 1920 x 1080@60Hz
Memory		2 x DDR4 2400 MHz, Max. 64GB
Storage		1 x 2.5" HDD/SSD (max. 9.5 mm) 1 x SD card
Expansion Slot		1 x M.2 2280, M Key 1 x M.2 2230, E Key
Video Output	HDMI Port	1 x HDMI 1.4
	VGA Port	1
I/O Port	USB 3.2 Gen1 (Bottom)	2
	USB 3.2 Gen1 (Side)	2
	USB 2.0 (Bottom)	2
	USB 2.0 (Side)	-
	COM Port	2 x RS232 (Max. 4)
	Line out/Mic in	1/1
Network	LAN	1 x Intel® Gigabit LAN
	Wifi	Realtek 802.11 a/b/g/n/ac Bluetooth 4.2
Communication	Webcam	2M FHD
	Microphone	Capacitor
	Speaker	2 x 2W
VESA Mount		Support 100 x 100 mm
Dimension (W/H/D) mm		391 x 327 x 42
Weight	NW (kg)	3.13
	GW (kg)	4.16
Certification		CB, CE, cTUVus, FCC, VCCI, TELEC, RCM, BSMI
Operating Temperature (°C)		0~40
Adapter		19V/3.42A 65W external adapter
Battery		-
Operating System		Windows 10 64bit, Linux
Optional Accessories		PCL71, POS01, WWN02
IP Level		Front Panel IP54