

## 深圳市迈迪杰电子科技有限公司

Shenzhen MADIGI electronic Technology CO., ltd

Product Spec			
Form Factory	Commercial Notebo	ok Product Specification	
Feature	Туре	Detailed Specification	
CPU	Intel	Tiger Lake UP3 refresh I3-1115G4 / I5-1155G7/ I7-1195G7, TDP 28w	
Memory	LPDDR4	LPDDR4, on board *4, up to 16GB total, 200ball	
LCD	Size	14inch	
	Resolution	1920x1200 16:10 FHD 300nits, sRGB 100%, 60Hz	
	Interface	eDP	
Audio	Audio Codec	Realtek ALC269Q-VC3-GR(VB6/VC3) Supprot DTS	
	Speaker	Build-in two speakers (4 $\Omega$ /2W)	
Storage	SSD	M.2 x1 Type 2280 Key M SSD, PCI-e interface (Gen 4) , Support 256GB/ 512GB 1TB	
Keyboard	US/UK	Support (with backlight) With number keys, backlight level 4 brightness adjustment, with case and case lights	
Touch Pad	12C	Dualpoint button (120x75MM)	
Finger Print		SPI interface (11MM) , Power button fingerprint identification, one-click login	
Sensor		Support light sensor (on camera)	
Wireless LAN	wifi	PCI-E interface, IEEE802.11 a/b/g/n/ac support wifi 6 ( intel AX200) BT5.1 or with 5 ( intel 9461 )	
Camera	USB interface	Built in camera module with D-Mic support2M webcam MICX2 ,LEDx1	
Power	Battery Pack	Li-Polymer, dump battery ,3 cells, 11.61V/ 5500 mAh 65Wh	
	AC-Adapter	65W (19V/3.42A) type-c with PD ( CE/CB Certification) c to c	
I/O	Kensington Lock	x1	
	Type-C	x1 (Charge )PD	
	HDMI 1.4	x1	
	USB 3.1	x1 (Gen 2, speed 10G)	
	Type-C	x1 (Charge&data&display)	
	USB3.0	x2 ( Gen1, speed 5G)	
	TF card	x1, USB2.0	
	Audio jack 3.5MM	x1	
	Reset Switch	x1	
Switch		Turn the camera on and off	
TPM		Support TPM 2.0	

System Status Indicator	Power LED Caps LED	Power On: White Full-charged: White Charging: Blinking White Low battery: blinking orange White (on keyboard)
Physical Outline	Dimension	<b>313.5 *227 *15.8MM</b> 1.4KG
	Hinge	180°hinge
OS		Support Windows 11 64 bits UEFI (Windows 11 Home Office suite) Support Linux Ubuntu
Certification	Certification	CE/CB/FCC/ Rohs